

Product Family	Product Name	Thickener Type	Base Oil Kinematic Viscosity @40 °C mm²/s	NLGI Grade	Recommended Operating Temperature Min /°C   Max /°C		
Mobilith SHC™ Series  • 3x the oxidation resistance compared to conventional mineral greases	Mobilith SHC™ 007	Lithium Complex	460	00	-50	150	
	Mobilith SHC™ 100	Lithium Comp <b>l</b> ex	100	2	-40	150	
<ul><li>Excellent low-temperature pumpability</li><li>Low starting and running torque</li></ul>	Mobilith SHC™ 220	Lithium Complex	220	2	-40	150	
Outstanding bearing protection under extreme pressures and heavy loads	Mobilith SHC™ 221	Lithium Complex	220	1	-40	150	
	Mobilith SHC™ 460	Lithium Comp <b>l</b> ex	460	1-2	-30	150	
	Mobilith SHC™ 1500	Lithium Complex	1500	1-2	-30	150	

## Mobilgrease XHP™ Series

- Highly adhesive structure reduces grease leakage and extends re-lubrication intervals
- Superb resistance to water washout
- Resistant to thermal and oxidative degradation at high temperatures



Mobilgrease XHP™ 220	Lithium Comp <b>l</b> ex	220	0	<b>-</b> 20	140
Mobilgrease XHP™ 221	Lithium Complex	220	1	-20	140
Mobilgrease XHP™ 222	Lithium Complex	220	2	<b>-</b> 20	140
Mobilgrease XHP™ 223	Lithium Complex	220	3	-10	140
Mobi <b>l</b> grease XHP™ 461, 462	Lithium Comp <b>l</b> ex	460	1,2	-20	140

## Mobilux™ EP Series

- Resistant to water washout and sprayoff
- Provides EP protection against wear and rust
- Good load carrying properties

Mobilux™ EP 0	Lithium	150	0	<b>-</b> 20	100
Mobilux™ EP 1, 2	Lithium	150	1,2	-30	120
Mobilux™ EP 3	Lithium	150	3	<b>-</b> 20	120
Mobi <b>l</b> ux™ EP 004	Lithium	150	00	-20	100

Polyurea

Polyurea



## Mobil SHC Polyrex™ EM Series

- Reduces bearing torque by up to 40% for higher motor efficiency
- Enhanced stability compared to conventional polyurea greases when subjected to mechanical shear forces
- Outstanding resistance to extreme high temperatures of up to 180°C
- Suitable for sealed-for-life ball bearings



Mobil SHC Polyrex™ 102 EM

Mobil SHC Polyrex™ 103 EM

87

87

-30

-20

180

180

